





CC-265-...

Electronic voltage detector60-150kV, red housing, 120 and 60mmdiameter electrode

Application:

- Electronic voltage detector for outdoor use with high resistance to shock, vibration and rain.
- Capacitive head technology, ulta compact.
- Operating voltage: 60 to 150 kV according to IEC 61243-1.

Features:

- Housing / electronic circuit design with guick release for easy battery replacement.
- Double signalling with presence of voltage indicated at the same time by:
 - · Bright red flashing light-emitting diodes (visible at more than 50 meters even in direct lighting),
 - Strong nominal acoustic signal (67 dB (A)/1,5 m).
 - 360° vision with illuminated display for optimum visibility.
- · Interchangeable contact electrodes.

Composition:

- Supplied with 3 end fittings for stick mounting:
 - · W: hexagonal 20 mm on flat;
 - · C: hexagonal 12 mm on flat;
 - K: universal.
- · Supplied with a shock-proof case with handle.

Optional accessories:

- Hook type contact electrode diam. 60 mm. Reference: CC-ANT60
- Hook type contact electrode diam. 120 mm. Reference: CC-ANT120
- Hook type contact electrode diam. 200 mm. Reference: CC-ANT200
- Recommended insulating sticks: CM-46, CE-430, CE-9











Référence	Voltage range	Frequency	Weight (kg)
CC-265-60/150	60 - 150 kV	50 / 60 Hz	1,2

Last Modification: 04/20/2025

