TABLE OF CHARACTERISTICS

	Voltage	Frequency	Threshold	Polarity DC	φ Indication	Continuity R	Continuity Tempo	Digital screen	Phase rotation	Lighting unit
		1		(D)	#			888	60	O;
MS-917-L	± 12 to 690 Vac / 750 Vdc	50 - 60 Hz	7 thresholds	~	~	200 Ω	×	×	×	×
MS-918-L	900 Vac / 1000 Vdc	50 - 60 and 400 Hz	8 thresholds	~	~	80 Ω	10s	×	~	V
MS-920-EX	690 Vac / 800 Vdc	50 - 60 Hz	Resolution 1 V	~	V	100 Ω	10s	V	~	V







10/20 Avenue Jean-Jaurès B.P.2 - 92222 BAGNEUX Cedex - France Phone : +33(0)1 42 31 46 46 www.catuelec.com

SICAME GROUP



SICAME GROUP

Detex*+



DC VOLTAGES
UP TO 1000Vdc

Polarity

Phase rotation indicator is more user friendly

Self-test



Ø 2 mm probes

UP TO 1000 Vdc 900 Vac

IP65 CATEGORY IV 600 V A LOW CONTINUITY RESISTANCE VALUE

ROBUST AND ERGONOMIC

With a high degree of sealing (IP65) and good impact resistance (IK06) our range is suitable for all environments.



SUITABLE FOR SAFETY PLUGS

> For 2P+T 10/16A with 19mm spacing.



A clear display

AC VOLTAGES

UP TO 900Vac

Phase indication

A wider voltage range for all your LV operations

SELF-TEST

Allows the complete check up of the voltage detector (batteries, leads, electronic). DIGITAL DISPLAY

MS-920 serie only.



AT HOME ANYWHERE

With its board hanger MS-920 serie only.

