

## CM-44...-

Insulated stick IEC 61235, Ø 39 mm (terminal elements)

### Application:

- Terminal element to be combined with the elements of the CM44 series (Base and Intermediate).
- Connectable by an insulated self-locking system made of aluminium alloy.

### Features:

- End-fittings: B, C, D, E, H, K or T. To be specified at the end of the reference.



| Ref.      | Length (mm) | Fitting | Weight (kg) |
|-----------|-------------|---------|-------------|
| CM-4410-B | 1200        | U3 male | 0,9         |
| CM-4415-B | 1160        | U3 male | 1,3         |
| CM-4420-B | 2200        | U3 male | 2,1         |
| CM-4425-B | 2700        | U3 male | 2,6         |
| CM-4410-C | 1140        | C       | 0,9         |
| CM-4415-C | 1700        | C       | 1,3         |
| CM-4420-C | 2140        | C       | 2,1         |
| CM-4425-C | 2640        | C       | 2,6         |
| CM-4410-D | 1210        | D       | 0,9         |
| CM-4415-D | 1640        | D       | 1,3         |
| CM-4420-D | 2210        | D       | 2,1         |
| CM-4425-D | 2710        | D       | 2,6         |
| CM-4410-E | 1110        | E       | 0,9         |
| CM-4415-E | 1710        | E       | 1,3         |
| CM-4420-E | 2110        | E       | 2,1         |
| CM-4425-E | 2615        | E       | 2,6         |
| CM-4410-H | 1130        | H       | 0,9         |
| CM-4415-H | 1610        | H       | 1,3         |
| CM-4420-H | 2130        | H       | 2,1         |
| CM-4425-H | 2630        | H       | 2,6         |
| CM-4410-K | 1130        | K       | 0,9         |
| CM-4415-K | 1630        | K       | 1,3         |
| CM-4420-K | 2130        | K       | 2,1         |
| CM-4425-K | 2630        | K       | 2,6         |
| CM-4410-T | 1130        | T       | 0,9         |
| CM-4415-T | 1660        | T       | 1,3         |
| CM-4420-T | 2160        | T       | 2,1         |
| CM-4425-T | 2660        | T       | 2,6         |