

CGM-3-.-410

Network Type : MV

Insulating gloves with mechanical protection and Arc Flash
12 cal/cm², class 3 - 26 500 V AC, length : 410 mm

Application:

- Wellfit finish: soft, supple, durable and ergonomic with high flexibility to ease the work.
- Convenient to any hand shape.
- Resistant: latex with reinforced mechanical protection against tearing. To be used without over-gloves.
- Protection against the thermal hazards of an electric arc 12 cal/cm². IEC 61482-1-2 APC 2 (box test 7 kA).

Features:

- Electrical insulating gloves, class 3 (26 500 V AC, 39 750 V DC).
- Cut edges.
- Material: bicolor natural latex. (exterior: orange, interior: natural).
- Traceability through flashcode on color-coded label. The color is according to the class.
- Category: RC (Acid, Ozone, Cold, Oil resistance).



Reference	Size	Length (mm)	Class	Voltage		ATPV (cal/cm ²)	Arc	Category
				Operating Voltage AC	Operating Voltage DC		Box Test	
CGM-3-08-410	8	410	3	26 500 V	39 750 V	12	7kA / 30 cm	RC
CGM-3-09-410	9	410	3	26 500 V	39 750 V	12	7kA / 30 cm	RC
CGM-3-10-410	10	410	3	26 500 V	39 750 V	12	7kA / 30 cm	RC
CGM-3-11-410	11	410	3	26 500 V	39 750 V	12	7kA / 30 cm	RC
CGM-3-12-410	12	410	3	26 500 V	39 750 V	12	7kA / 30 cm	RC