



Standards

IEC 61482-2 APC2 & ATPV 25-40 cal/cm² ISO 11612 A B1 C2 F2 EN 1149-5 NFPA 70E - ASTM F1959

AFG-4300-...

CAT'ARC multi-risk switching jacket to protect against an electric arc APC2 ATPV 25-40 cal/cm² size L

Application :

- Especially designed to be worn on top of the usual clothing, for short operations (eg. power-breaking operations).
- Prevention of the worsening of an accident by quickly and easly removing the jacket thanks to the red anti-panic zip.

Features :

- To wear with the hood AFG-HOOD-4.
- A back lenght of 121 cm to ensure an efficient protection of the operator down to the knees.
- · Pictograms of the standards clearly visible on the left sleeve.





| Reference | Size | ATPV (cal/cm²) | Arc |
|------------|------|----------------|-------------|
| | | | Box Test |
| AFG-4300-L | L | 40 | APC 2 |
| | | | |



Last Modification : 08/05/2025

UID : | TID : :: 08/30/2025| SID : :: 08/30/2025 | Issued :08/30/2025 12:04:36 pm

CATU S.A.S. - 10, Avenue Jean-Jaurès - B.P.2 - 92222 Bagneux Cedex France Phone : +33 1 42 31 46 00 - Fax : +33 1 42 31 46 32

