

Z-VAT-DC / CL-6

Network Type : MV-LV

DC bipolar voltage detector

Application:

Solution for checking the absence of voltage on a DC-powered network:

- Presence of voltage indicated by the lighting up of 6 red LEDs and the emission of an audible signal.
- Function control of the integrated device which validates all detector functions. :
 - Contact the handle's magnetic shoe with the rail and shunt the assembly by making contact between the magnetic handle and the contact hook;
 - Press the test button: 6 red LEDs light up, audible signal sounds;
 - Release the test button: momentary illumination of the 6 green LEDs.

Features:

The solution includes:

- Acoustic and luminous DC voltage detector;
- Rail clamp or magnetic contact stud;
- Various types of end caps and/or poles;
- Connection cable.



Référence	Weight (kg)
Z-VAT-DC-1000-RSL	5,950
Z-VAT-DC-120/1500-HS	6,900
Z-VAT-DC-120/1500-U	4,000
Z-VAT-DC-120/2200-PS	4,200
Z-VAT-DC-120/2200-S	3,800
Z-VAT-DC-750/1500	3,400
Z-VAT-DC-750/1500-W	6,620
Z-VAT-DC-750/1500-WO	6,500
Z-VAT-DC-2000-HS	2,200
Z-VAT-DC-2000-RS	6,300
Z-VAT-DC-2000-TS	2,100
Z-VAT-DC-3000/1-HS	6,000
Z-VAT-DC-4000-HS	6,100
Z-VAT-DC-5000-P	1,700
Z-VAT-DC-IND	3,500
Z-VAT-DC-IND-E	3,500
CL-6-100/30000	4,300
CL-6-120/5000	2,000