

## MX-750...

Network Type : LV

### Multifunction installation tester

#### Application:

- Insulation resistance
- Earth resistance
- Low impedance continuity
- Loop Impedance
- Voltage
- RCD

#### Features:



	Plage Range Rango	Résolution Resolution Resolución	Précision Accuracy Precisión
Impédance de boucle Loop resistance Resistencia del bucle (Hi-Amp)	0.23-9.99 Ω	0.01 Ω	
	10.0-99.9 Ω	0.1 Ω	±(4% of reading +6 digits)
	100-999 Ω	1 Ω	
L- PE Sans déclenchement No trip Sin gatillo	0.23-9.99 Ω	0.01 Ω	
	10.0-99.9 Ω	0.1 Ω	±(5% of reading +6 digits)
	100-999 Ω	1 Ω	
Impédance de ligne Line resistance Resistencia lineal L-N	0.23-9.99 Ω	0.01 Ω	
	10.0-99.9 Ω	0.1 Ω	±(4% of reading +4 digits)
	100-999 Ω	1 Ω	
	Multiplicateur Current Multiplier Multiplicador	Précision sur le temps de déclenchement Trip Time Accuracy Tiempo de precisión de activación	
	x1/2	±(1% of reading+1 ms)	
RCD (BSEN 61557-6) RCD Rating (L-N): 10mA, 30mA, 100mA, 300mA, 500mA, 650mA, 1A	x1	± (1% of reading + 1 ms)	
	x2	±(1% of reading+1 ms)	
	x5	±(1% of reading+1 ms)	

	Tension d'essai Test voltage Prueba de tensión	Plage Range Rango	Résolution Resolution Resolución	Précision Accuracy Precisión	Courant de test Test current Corriente de prueba	Courant de court-circuit Short circuit current Corriente de cortocircuito
<b>Isolement Insulation Aislamiento</b>	125V (0% +10%)	0.125 1 000 MΩ	0.001 MΩ	± (2%+10)	1 mA load 125 kΩ	≤ 1mA
	250V (0% +10%)	0.250 1 000 MΩ	0.001 MΩ	± (2%+10)	1 mA load 250 kΩ	
	500V (0% +10%)	0.500 1 000 MΩ	0.001 MΩ	± (2%+10)	1 mA load 500 kΩ	
	1 000V (0% +10%)	1.000 1 000 MΩ	0.001 MΩ	± (3%+10)	1 mA load 1 MΩ	
		Plage Range Rango	Résolution Resolution Resolución	Précision Accuracy Precisión	Tension max. ouverte Max. open circuit voltage Tensión máx. abierta	Protection de surcharge Overload protection Protección contra sobrecargas
<b>Basse résistance Low Ohm baja resistencia</b>		0.000-2.000 Ω	0.0010 Ω	±(1.5%+30)	5.0V±1VDC	250Vrms
		2.00-20.00 Ω	0.010 Ω	±(1.5%+3)		
		20.0-200.0 Ω	0.10 Ω			
		200-2 000 Ω	10 Ω	±(1.5%+5)		
<b>Résistance de mise à la terre Earth resistance Resistencia de puesta a tierra</b>		0.00-99.99 Ω	0.010 Ω	±(2%+30d)		
		100.0-999.9 Ω	0.10 Ω	±(2%+6d)		
		1 000-2 000 Ω	1 Ω			

**Composition:**

- 1 Multifunction Installation Tester
- User Manual
- Software CD
- Remote Control Probe
- Test Leads
- Mains Measuring Cable
- Crocodile Clips
- USB Cable
- Carrying Case
- Soft Carrying Neck Belt



Référence

**MX-750**