

Standards

Casque/ Helmet : EN 397
 EN 50365 1000 V AC
 1500 V DC Ecran/
 Faceshield : Arc flash GS-
 ET-29 APC 2 ASTM
 F2178 ATPV 14 cal/cm²
 EN 166/EN 170 2C-2
 CATU 1B 3 8 2 2

MO-180-ARC-..

Replacement arc flash face shield and chin cup protection for MO-180-ARC-12, APC2 - 12 cal/cm²

Application:

- Unique patented solution by CATU to protect eyes, face and head against thermal arc hazards of an electric arc.

Features:

- Insulating protection of the shell up to 20 kV (ANSI) and protection against mechanical shocks.
- Thermal arc protection according to both test methods:
 - APC (Arc Performance Class);
 - ATPV (Arc Thermal Performance Value).
- Face shield protection against electrical arc, fully retractable inside the shell.
- Chin-strap with 4 attachment points for comfortable ear positioning and with user friendly clip locking system.
- Adjustable size by mean of a ratchet.



| Reference | Description | ATPV (cal/cm ²) | Arc |
|---------------------|---|-----------------------------|----------|
| | Composition | | Box Test |
| MO-180-ARC-12-VI-CC | Replacement arc flash face shield + chin cup protection | 12 | APC 2 |