

## MV-226-..

Safety shoes with insulating sole, textile and low type

### Application:

- Safety shoes, low, textile model, with 1000 V AC insulating sole according to RTE SERECT ST HTA 70A ind E § 3.4.
- Ventilated shoes for comfortable use in hot environments, indoors or on dry ground.
- Shoes with insulated soles specially designed for electricians, industry, logistics and transport, crafts.



### Features:

- Shoes with "3D mesh ventilated quarters" upper.
- Sole: PU/nitrile rubber.
- Front and rear leather reinforcements.
- Breathable, absorbent anti-bacterial lining.
- Metal-free protective toe cap.
- SB: basic protection.
- HRO: direct contact heat resistance.
- SRC (SRA + SRB) : Adhesion, slip resistance on ceramic tiles and steel floor.
- E: Heel energy absorption capacity.
- FO: Resistance to hydrocarbons.
- Unit test of each shoe before dispatch in accordance with RTE SERECT specification No. ST HTA ind E to validate resistance to test voltage: 5 kV/1 min.

| Reference | Size | Voltage              | Weight (kg) |
|-----------|------|----------------------|-------------|
|           |      | Operating Voltage AC |             |
| MV-226-40 | 40   | 1 000 V              | 1,29        |
| MV-226-41 | 41   | 1 000 V              | 1,34        |
| MV-226-42 | 42   | 1 000 V              | 1,39        |
| MV-226-43 | 43   | 1 000 V              | 1,5         |
| MV-226-44 | 44   | 1 000 V              | 1,9         |
| MV-226-45 | 45   | 1 000 V              | 1,56        |
| MV-226-46 | 46   | 1 000 V              | 1,5         |
| MV-226-47 | 47   | 1 000 V              | 1,62        |