# **GATU** Sicame Group



Standards ISO 20345 SB HRO SRC E FO RTE SERECT ST HTA 70A ind E § 3.4 MAX 1 000 V AC

## MV-226-..

## Safety shoes with insulating sole, textile and low type

### **Application:**

- Safety shoes, low, textile model, with 1000 V AC insulating sole according to RTE SERECT ST HTA 70A ind E § 3.4.
- Ventilated shoes for comfortable use in hot environments, indoors or on dry ground.
- Shoes with insulated soles specially designed for electricians, industry, logistics and transport, crafts.



#### **Features:**

- Shoes with "3D mesh ventilated quarters" upper.
- Sole: PU/nitrile rubber.
- Front and rear leather reinforcements.
- Breathable, absorbent anti-bacterial lining.
- Metal-free protective toe cap.
- SB: basic protection.
- HRO: direct contact heat resistance.
- SRC (SRA + SRB) : Adhesion, slip resistance on ceramic tiles and steel floor.
- E: Heel energy absorption capacity.
- FO: Resistance to hydrocarbons.
- Unit test of each shoe before dispatch in accordance with RTE SERECT specification No. ST HTA ind E to validate resistance to test voltage: 5 kV/1 min.

Reference	Size	Voltage	Weight (kg)
		Operating Voltage AC	
MV-226-41	41	1 000 V	1,34



UID : | TID : :: 01/01/1970| SID : :: 01/01/1970 | Issued :05/02/2025 01:27:11 am

CATU S.A.S. - 10, Avenue Jean-Jaurès - B.P.2 - 92222 Bagneux Cedex France Phone : +33 1 42 31 46 00 - Fax : +33 1 42 31 46 32

