



Standards
ISO 20345 SB HRO SRC
E FO
RTE SERECT ST HTA
70A ind E § 3.4 MAX 1
000 V AC

MV-227-..

Safety shoes with insulating sole, textile and high type

Application:

- Safety shoes, high, textile model, with 1000 V AC insulating sole according to RTE SERECT ST HTA 70A ind E § 3.4.
- Ventilated shoes for comfortable use in hot environments, indoors or on dry ground.
- Shoes with insulated soles specially designed for electricians, industry, logistics and transport, crafts.



Features:

- Shoes with "3D mesh ventilated quarters" upper.
- · Sole: PU/nitrile rubber.
- Front and rear leather reinforcements.
- · Breathable, absorbent anti-bacterial lining.
- Metal-free protective toe cap.
- · SB: basic protection.
- HRO: direct contact heat resistance.
- SRC (SRA + SRB): Adhesion, slip resistance on ceramic tiles and steel floor.
- E: Heel energy absorption capacity.
- FO: Resistance to hydrocarbons.
- Unit test of each shoe before dispatch in accordance with RTE SERECT specification No. ST HTA ind E to validate resistance to test voltage: 5 kV/1 min.

		Voltage	
Reference	Size	Operating Voltage AC	Weight (kg)
MV-227-40	40	1 000 V	1.47

 $\mbox{UID}: |\mbox{TID}: :: 01/01/1970| \mbox{SID}: :: 01/01/1970 \ | \mbox{Issued}: 05/02/2025 \ 01:27:22 \ \mbox{am}$

Last Modification: 12/26/2024

222 Bagneux Cedex
France
:+33 1 42 31 46 32