

CC-265-...

Voltage detector, high voltage HV - 90-225 kV, Ø electrode 120 mm

Application:

- Electronic voltage detector for outdoor use with high resistance to shock, vibration and rain.
- Capacitive head technology, ultra compact.
- Operating voltage: 90 to 225 kV according to IEC 61243-1.

Features:

- Housing / electronic circuit design with quick release for easy battery replacement.
- Double signalling with presence of voltage indicated at the same time by:
 - Bright red flashing light-emitting diodes (visible at more than 50 meters even in direct lighting),
 - Strong nominal acoustic signal (67 dB (A)/1,5 m).
 - 360° vision with illuminated display for optimum visibility.
- Interchangeable contact electrodes.

Composition:

- Supplied with 3 end fittings for stick mounting:
 - W: hexagonal 20 mm on flat ;
 - C: hexagonal 12 mm on flat ;
 - K: universal.
- Supplied with a shock-proof case with handle.

Optional accessories :

- Hook type contact electrode diam. 60 mm. Reference: CC-ANT60
- Hook type contact electrode diam. 120 mm. Reference: CC-ANT120
- Hook type contact electrode diam. 200 mm. Reference: CC-ANT200
- Recommended insulating sticks: **CM-46**, **CE-430**, **CE-9**



Référence	Voltage range	Frequency	Weight (kg)
CC-265-90/225	90 - 225 kV	50 / 60 Hz	1,2