



**Standards** EN 60903:2003 IEC 60903:2014 IEC 61482-2 ASTM F2675

Network Type : MV

## CGM-3..

Insulating gloves with mechanical protection and Arc Flash 12 cal/cm<sup>2</sup>, class 3 - 26 500 V AC, length : 360 mm

## **Application:**

- · Wellfit finish: soft, supple, durable and ergonomic with high flexibility to ease the work.
- Convenient to any hand shape.
- · Resistant: latex with reinforced mechanical protection against tearing. To be used without over-gloves.
- Protection against the thermal hazards of an electric arc 12 cal/cm<sup>2</sup>. IEC 61482-1-2 APC 2 (box test 7 kA).

## **Features:**

- Electrical insulating gloves, class 3 (26 500 V AC, 39 750 V DC).
- · Cut edges.
- Material: bicolor natural latex. (exterior: orange, interior: natural).
- Traceability through flashcode on color-coded label. The color is according to the class.
- Category: RC (Acid, Ozone, Cold, Oil resistance).



Reference	Size	Length (mm)	Class	Voltage			Arc	
				Operating Voltage AC	Operating Voltage DC	ATPV (cal/cm²)	Box Test	Category
CGM-3-11	11	360	3	26 500 V	39 750 V	12	7kA / 30 cm	RC



Last Modification : 12/26/2024



UID : | TID : :: 01/01/1970| SID : :: 01/01/1970 | Issued :05/01/2025 12:09:55 pm

CATU S.A.S. - 10, Avenue Jean-Jaurès - B.P.2 - 92222 Bagneux Cedex France Phone : +33 1 42 31 46 00 - Fax : +33 1 42 31 46 32

