





KIT-MO68404DYN/ M-883145-...

Insulated Torque screwdriver kit

Application:

- Tool kit for tightening 4mm hexagonal hollow screws, designed for live working applications.
- Compliant with the IEC 60900 standard, it supports safe operation at voltages up to 1000 V AC and 1500 V DC
- Kit designed for the mounting of the circuit breakers, counters and various kits used by ENEDIS for the equipment of control panels.

Features:

- Maximum operating voltage: 1 000 V AC 1 500 V DC.
- The screwdriver is torque-limited to 4Nm.
- · The handle is articulated:
 - In the straight position, it is ideal for initial tightening.
 - In the angled position, it is suited for screwing with tightening torque.
- When torque is reached the screwdriver will disengage and automatically reset itself.
- · Over tightening is not possible after 4Nm.
- · The screwdriver can also be used for loosening screws

Composition:

- 1 torque limited (4 Nm) screwdriver MO-68404DYN.
- 1 short hex blade for MO68404DYN.
- 1 long hex blade for MO68404DYN.
- 1 flat blade 6.5mm for MO68404DYN.
- 1 storage bag







Ref	Dimensions	Weight (kg)	Voltages for use	
			Operating Voltage AC	Operating Voltage DC
MO-68404DYN	260 x 70 x 50	0.3	1 000 V	1 500 V

Last Modification: 11/13/2025



UID: | TID::: 12/28/2025 | SID::: 12/28/2025 | Issued: 12/28/2025 02:52:31 pm