

MS-917-..

Network Type : LV

Low Voltage detector DETEX

Application:

- Check the presence of voltage.
- Checks voltage levels from 12 to 900 V AC, 1 000 V DC (according to models).
- Sound and light continuity for a non-live circuit (threshold of 200 Ω).
- Search for the polarities of a DC circuit.
- Unipolar phase identification.
- For indoor/outdoor use.

Features:

- Fitted with IP2X test lead points with retractable trigger tips (MS-917-PG) or retractable sleeves (MS-917 and MS-917-BS). Test lead points $\varnothing$ 2 mm L: 19 mm (MS-917-L)
- Total safety with hazardous voltage indicator light (> 50 V).
- Protection level: IP65/IK06.
- Self test button to discern the verification of the good functioning and the continuity function.
- Completely modular and adjustable to eclipse sockets.
- LED display.

Composition:

- MS-917-PG and MS-917-ET: supplied with soft carrying case and belt loop Ref. M-87285.

Optional accessories:

- 2 test plug adapters to be fixed on IP2X test lead points with retractable trigger tips enabling to target test plugs $\varnothing$ 4 mm. Ref. DX-04
- Carrying bag with belt loop, Ref. M-87285.
- Holder, Ref. M-952325.
- Contact probes for L.V. detectors for installation and sidewalk boxes. Ref. M-8013.
- Contact probes for L.V. detectors for flight path. Ref. M-8014.
- Hand stick & stick extension. Ref. M-951143.



Référence	Frequency	Weight (kg)
MS-917/2-ERDF	50/60 Hz	0,225