

PP-6-38-R-..

Insulated safety padlock, nylon shackle 38 mm, diameter 6 mm

Application :

- For locking separating devices (e.g. circuit breakers) in order to prevent their operation.
- Padlock with insulating shackle for use in low voltage 1000 V AC - 1500 V DC: tested and validated in accordance with the electrical test IEC 60900 (2012) §5.5.3.
- More secure locking: impossible to drop the key when the shackle is open, the key remains trapped.



Features :

- Available with keys alike, random (Z) keys.
- Marking on both sides :
 1. On one side: Standard symbol.
 2. On the other side: area for marking the user's name and contact details.
- Padlocks delivered with 2 keys.

Ref.	Description		Diameter	Characteristics
	Color	Key Number	Shackle	Weight
PP-6-38-R-..	■	Aléatoire : Z / Identique : A1, A2, A3, A4, A5	6	92g
PP-6-38-R-A1	■	Aléatoire : Z / Identique : A1, A2, A3, A4, A5	6	92g
PP-6-38-R-A2	■	Aléatoire : Z / Identique : A1, A2, A3, A4, A5	6	92g
PP-6-38-R-A3	■	Aléatoire : Z / Identique : A1, A2, A3, A4, A5	6	92g
PP-6-38-R-A4	■	Aléatoire : Z / Identique : A1, A2, A3, A4, A5	6	92g
PP-6-38-R-A5	■	Aléatoire : Z / Identique : A1, A2, A3, A4, A5	6	92g