

PP-6-38-...

Insulating safety padlock with retaining key, nylon shackle H 38 mm diameter 6 mm

Application :

- For locking the separating devices (e.g. circuit breakers) to prevent their operation.
- Padlock with insulating shackle for use in low voltage 1 000 V AC 1 500 V DC: tested and validated in accordance with the electrical test IEC 60900 (2012) §5.5.3.
- More secure locking: impossible to drop the key when the shackle is open, the key remains trapped.

Features :

- Available with keys alike (A.) or keys different (Z).
- Marking on both sides :
- 1. On one side: Standard symbol.
- 2. On the other side: area for marking the user's name and contact details.
- Padlocks delivered with 2 keys.

| Ref. | | Description | Diameter | Characteristics |
|-------------|-------|---------------|----------|-----------------|
| | Color | Key Number | Shackle | Weight |
| PP-6-38-R-Z | | Z | 6 | 92g |



| Last | Modification | on : | 10/07/2024 |
|------|--------------|------|------------|
|------|--------------|------|------------|

UID : | TID : :: 01/01/1970| SID : :: 01/01/1970 | Issued :05/02/2025 01:27:19 am

CATU S.A.S. - 10, Avenue Jean-Jaurès - B.P.2 - 92222 Bagneux Cedex France Phone : +33 1 42 31 46 00 - Fax : +33 1 42 31 46 32

