

CC-765-...

Network Type : MV

Voltage detector, compact series, 63-90 kV, C (hexagonal 12 mm) end fitting

Application:

- Electronic voltage detector for indoor and outdoor use, with high level of shock, vibration and rain resistance.
- Capacitive head technology, ultra compact.
- Broad voltage range, operating frequency 50 and 60 Hz.

Features:

- Robust thermoplastic housing.
- Voltage presence signaled by:
 - Flashing red LEDs;
 - Powerful audible signal (67 dB (A)/1.5 m);
 - Visible over 360° with lighting and display.
- Contact electrodes easily interchangeable.

Composition:

- Supplied with an end-fitting matching the insulating stick terminal:
 - C: hexagonal 12 mm for sticks with C fitting;
 - K: universal for sticks with K fitting;
 - U: UDI end-fitting with a U shape (55 mm overhang) for sticks with UDI end-fitting.
- CC-765-44/132 & 63/90 versions are supplied with 1 hook-shaped contact electrode \varnothing 120 mm, Ref. [CC-ANT120](#)
- Supplied in a carrying case.

Optional accessories:

- Recommended insulating sticks: [CE-4-21](#), [CE-75](#) series.



Référence	Description	Voltage range	Frequency	Weight (kg)
	Fitting			
CC-765-63/90-C	C	63 - 90 kV	50 / 60 Hz	0,35