



Standards ISO 20345 SB HRO SRC E FO RTE SERECT ST HTA 70A ind E § 3.4 MAX 1 000 V AC



## Safety shoes with insulating sole, textile and high type

## **Application:**

- · Safety shoes, high, textile model, with 1000 V AC insulating sole according to RTE SERECT ST HTA 70A ind E § 3.4.
- Ventilated shoes for comfortable use in hot environments, indoors or on dry ground.
- Shoes with insulated soles specially designed for electricians, industry, logistics and transport, crafts.



## **Features:**

- Shoes with "3D mesh ventilated quarters" upper.
- Sole: PU/nitrile rubber.
- Front and rear leather reinforcements. •
- Breathable, absorbent anti-bacterial lining.
- Metal-free protective toe cap.
- SB: basic protection.
- HRO: direct contact heat resistance. •
- SRC (SRA + SRB) : Adhesion, slip resistance on ceramic tiles and steel •
- floor.
- E: Heel energy absorption capacity.
- FO: Resistance to hydrocarbons.
- Unit test of each shoe before dispatch in accordance with RTE SERECT • specification No. ST HTA ind E to validate resistance to test voltage: 5 kV/1 min.

Reference	Size	Voltage	- Weight (kg)
		Operating Voltage AC	
MV-227-42	42	1 000 V	1.49



www.catuelec.com

UID : | TID : :: 05/03/2025| SID : :: 05/03/2025 | Issued :05/03/2025 02:25:55 am

