Standards
IEC 61481-1:2014

CL-7-...

HV one pole phase testing range. 4-18 kV. Class C with buzzer



Application:

- Single-pole HV phase match checker.
- Maximum operating voltage: 18 kV.

Features:

- Single-pole device with C, K and W end-fitting.
- Storage of frequency and phase of distribution network voltages.
- Push-button test of the device, which also resets the memory.
- Class C (maximum time for storing information in memory: 15 s when not connected to the line).
- Non accordance: +110° to +250°.
- LED indicators:
  - **Orange** (M) indicating the storage of a phase and the mains frequency;
  - **Green** (C) indicating that the mains phase is identical to the one previously stored (match); + discontinuous beep buzzer.
  - **Red** (I) indicating that the phase of the network is of a different phase from that previously stored (mismatch) + continuous beep buzzer.
- Voltage difference between the two networks to be compared: +/- 15 %.
- Angle difference between the two phases (networks) to be compared: +/- 10°.
- The red ring indicates the physical limit to which the phase comparator can be inserted between live parts (57 cm from the red ring to the end fitting).
- NFC Tag.

Composition:

- Supplied in a back rigid box.
- Battery: 9 V (6LR61).

Optional accessories:

- Antenna Magnefix with a U Max utilisation : 18 kV, Ref C-921545.





Référence	Description	Dimensions	Frequency	Weight (kg)
	Fitting	Length (mm)		
CL-7-4-18	C - K - W	790	50 / 60 Hz	1,05

AFG-2001-...

CATU S.A.S. - 10, Avenue Jean-Jaurès - B.P.2 - 92222 Bagneux Cedex
France
Phone : +33 1 42 31 46 00 - Fax : +33 1 42 31 46 32

Estándar
IEC 61482-2 APC 1 &
ATPV 12 cal/cm² ISO
11612 A B1 C1 F1 ISO
11611 class 1 EN 1149-5
NFPA 70E - ASTM F1959

Pantalón CAT'ARC



Utilización:

- Protección múltiple contra riesgos térmicos por arcos eléctricos, calor y llamas, soldadura y descargas electroestáticas.
- Se adapta a todo tipo de morfologías: cintura elástica, largura de la entrepierna ajustable (77 o 82 cm).

Características:

- ATPV: 12 cal/cm2.
- APC: clase 1 (4 KA/30 cm).
- A combinar con la chaqueta de protección CAT'ARC **AFG-2000...**
- 2 bolsillos italianos y 2 bolsillos cargo.
- Rodillas, cremalleras y entrepierna reforzadas para minimizar riesgos de rotura.

Referencia a completar con la talla deseada.

Ejemplo: AFG-2001-XL para el pantalón en talla XL.





Referencia	Talla	APTV (cal/cm2)	Box test	Couleur
AFG-2001-XS	XS	12	APC 1	
AFG-2001-S	S	12	APC 1	
AFG-2001-M	M	12	APC 1	
AFG-2001-L	L	12	APC 1	
AFG-2001-XL	XL	12	APC 1	
AFG-2001-2XL	2XL	12	APC 1	
AFG-2001-3XL	3XL	12	APC 1	
AFG-2001-4XL	4XL	12	APC 1	
AFG-2001-5XL	5XL	12	APC 1	

CATU S.A.S. - 10, Avenue Jean-Jaurès - B.P.2 - 92222 Bagneux Cedex
France
Phone : +33 1 42 31 46 00 - Fax : +33 1 42 31 46 32